

SITEMATE SM16.10

32 Amp Temporary Power Distribution Unit

APPLICATIONS:

- Used for temporary power reticulation
- Construction Industry
- Heavy Industry
- Indoor / outdoor events
- Ports

CONSTRUCTION:

- 10 x 15A single phase 3 pin socket outlets
- 1 x 32A 3 phase + N + E, 415Va.c socket outlet
- 1 x 16A Single phase 2P + E, IEC 60309 socket outlet
- Supply - 32A 3ph + N + E 415Va.c IEC 60309
- Frequency 50 - 60Hz
- RCD - 4 Pole, 30mA, 40A 415Va.c
- RCBO - 2 Pole, 30mA, 16A 230Va.c
- Interconnection - 32A 3 phase + N + E 415Va.c IEC 60309
- IP44 / IP65
- Includes 10kA RCD and 15kA MCB as standard
- Specially blended polyethylene enclosure
- Meets AS/NZS 61439.4 requirements for assemblies for construction sites.
- **Dimensions** - 634mm (L) x 500mm (H) x 501mm (W)

PRODUCT FEATURES:

- 2 Year Limited Warranty.
- Stackable for storage and transportation.
- 85mm ground clearance.
- Third party tested.
- Impact resistant robust enclosure for outdoor use.
- Recessed design to minimise potential damage to outlets.
- Anchoring points
- Industrial sockets can be replaced without opening unit
- Designed for reduced maintenance costs
- Dual handles for easy lifting and cable management
- Stable foot print to minimise risk of toppling
- Customisation available on request
- Assembled with trade tested components
- Designed for NZ & AU conditions.



Code	Supply Power	Socket Outlets	Weight
SM16.10	32A, 3 Phase + N + E 415Va.c IEC 60309	10 x 15A single phase 3 pin, 1 x 32A 3 phase + N + E, 1 x 16A 1ph 2P + E IEC 60309	20kgs

Sitemate Power Systems has taken every precaution to ensure accurate information on this data page, but accept no liability for any errors or omissions. Sitemate Power Systems reserves the right to modify specifications at any time.