

**SM16**  
**- 32 AMP TEMPORARY POWER DISTRIBUTION UNIT**



**APPLICATIONS**

- Used for temporary power reticulation
- Construction industry
- Heavy industry
- Indoor/outdoor events
- Ports

**CONSTRUCTION**

- 8 x 15A single phase 3P socket outlets
- 1 x 32A 3 phase + N + E, 415VAC socket outlet
- 1 x 16A single phase 2P + E, IEC 60309 socket outlet
- Supply – 32A 3 phase + N + E, 415VAC IEC 60309
- Frequency 50 – 60Hz
- RCD – 4 pole, 30mA, 40A 415VAC
- RCBO – 2 pole, 30mA, 16A 230VAC
- Interconnection – 32A 3 phase + N + E, 415VAC IEC 60309
- IP44/IP65
- Includes 10kA RCD and 10kA MCB as standard
- Specially blended polyethylene enclosure
- Meets AS/NZS 61439.4 requirements for assemblies for construction sites
- Dimensions – 634mm (L) x 500mm (H) x 501mm (W)

**PRODUCT FEATURES**

- 2 year limited warranty
- Stackable for storage and transportation
- 85mm ground clearance
- Third party tested
- Impact resistant robust enclosure for outdoor use
- Recessed design to minimise potential damage to outlets
- Anchoring points
- Industrial sockets can be replaced without opening unit
- Designed for reduced maintenance costs
- Dual handles for easy lifting and cable management
- Stable foot print to minimise risk of toppling
- Customisation available on request
- Assembled with trade tested components
- Designed for NZ & AU conditions

Product Code	Supply Power	Socket Outlets	Weight (kg)
SM16	32A, 3 phase + N + E, 415VAC IEC 60309	8 x 15A single phase 3P, 1 x 32A 3 phase + N + E, 1 x 16A single phase 2P + E, IEC 60309	19