

Wall Mounted Socket Outlet Enclosures

SMWB - WALL MOUNTED SOCKET OUTLET ENCLOSURE



SMWB41



SMWB51



SMWB52

APPLICATIONS

- Generator power distribution
- Construction site boards
- Workshop power distribution
- Refrigerated container distribution
- Cool-store trailer power

CONSTRUCTION

- GRP base with high quality Mitsubishi plastic front panel
- IP66 enclosure – weather proof for outdoor use
- Industrial connectors to maintain IP rating
- Quality Eaton safety switchgear for personal protection and reliability
- Built tough for industry

PRODUCT FEATURES

- 2 year limited warranty
- Customisation available on request
- IP66
- IK09 Impact rating
- Externally moulded feet to maintain IP rating
- Hinged door for easy access and safer testing
- Threaded 'Punch out' holes for faster installation
- Modular options available

Product Code	Size W x H x D (mm)	Outlets		
		Quantity	Voltage (VAC)	Configuration
SMWB41	225 x 425 x 170	2 1	230 400	15A, 2P+E AS/NZS (RCD protected) 32A, 3P+N+E AS/NZS (RCD protected)
SMWB51	260 x 500 x 170	2 1	230 400	15A, 2P+E AS/NZS (RCD protected) 32A, 3P+N+E AS/NZS (RCD protected) with 32A isolator switch
SMWB52	260 x 500 x 170	4	400	32A, 3 phase + E, IEC 60309 Reefer socket