

TUFFLITE TPIL® Temporary Lighting

TUFFLITE TPIL® SMTL10012 / SMTL20025 – LED – TEMPORARY PROTECTED INSTALLED LIGHTING®



Plug Options



16A IEC 2P + E



10A Flat Pin 2P + E



15A Flat Pin 2P + E

APPLICATIONS

- Construction and demolition sites
- Indoor/outdoor events
- Compatible with Sitemate® temporary power distribution equipment

CONSTRUCTION

- Meets AS/NZS 60598.1 & 60598.2.20 for Temporary Protected Installed Lighting chains
- Class II luminaire suitable for rough service
- IP65 suitable for outdoor use
- Impact tested to IK08
- Continuous earth
- Heavy duty flexible cable 2.5mm 2 core + E, H07RN-F rubber sheath

PRODUCT FEATURES

- 2 year limited warranty
- Third party tested and certified
- Efficient LED lamps
- 20 Watt output per fitting
- 2000 Lumens per fitting
- 100 Watt output per 12m chain
- 200 Watt output per 25m chain
- Tough zinc plated protective cover
- Opaque white polycarbonate lens
- Interconnects up to 60 x fittings or 6 x 25m chains
- Luminaire replaceable if required

Product Code	Plug & Connector	Length (m)	Colour Temp (K)	Lumens Per Fitting (lm)	Voltage (VAC)	Output Per Fitting / Chain Watts (W)	Light Fitting Per Chain (pcs)	Weight (kg)
SMTL10012IEC16	16A IEC 2P + E	12	5000	2000	240	20 / 100	5	5.5
SMTL10012NZS10	10A Flat Pin 2P + E	12	5000	2000	240	20 / 100	5	5.5
SMTL10012NZS15	15A Flat Pin 2P + E	12	5000	2000	240	20 / 100	5	5.5
SMTL20025IEC16	16A IEC 2P + E	25	5000	2000	240	20 / 200	10	11
SMTL20025NZS10	10A Flat Pin 2P + E	25	5000	2000	240	20 / 200	10	11
SMTL20025NZS15	15A Flat Pin 2P + E	25	5000	2000	240	20 / 200	10	11

Chain & Rigging has taken every precaution to ensure accurate information on this data page, but accept no liability for any errors or omissions. Chain & Rigging reserves the right to modify specifications at any time.