

SM7.01

- 32 AMP TEMPORARY POWER DISTRIBUTION UNIT

APPLICATIONS

- Used for temporary power reticulation
- Construction industry
- Heavy industry
- Indoor/outdoor events
- Ports

CONSTRUCTION

- 6 x 15A sockets single phase 3P
- Supply 32A 3 phase + N + E, 230VAC IEC 60309
- Interconnection 32A 3 phase + N + E, 230VAC IEC 60309
- Frequency 50 60Hz
- RCD 2 pole, 30mA, 32A 230V
- IP44/IP65
- Includes 10kA RCD and 10kA MCB as standard
- Specially blended polyethylene enclosure
- Meets AS/NZS 61439.4 requirements for assemblies for construction sites
- Dimensions 517mm (L) x 280mm (H) x 268mm (W)



- 2 year limited warranty
- Stackable for storage and transportation
- 40mm ground clearance
- · Third party tested
- Impact resistant robust enclosure for outdoor use
- Assembled with standard industrial sockets allowing hassle free replacement
- Customisation available on request
- Assembled with trade tested components
- Designed for NZ & AU conditions
- Anti-theft locking ring available on request

Product Code	Supply Power	Socket Outlets	Weight (kg)
SM7.01	32A, single phase + N + E, 230VAC IEC 60309	6 x 15A single phase 3P	8



Model: SM7.01 - Single Phase Supply